

PL 30 D

RFID Access Control and Time Attendance Terminal

- 2.4 inch colorful screen display.
- Multiple menu languages & voice.
- USB flash drive to download or upload employee details.
- Anti-passback, Anti-tamper, Cloud web (ADMS).
- 10,000 RFID Card capacity, 200,000 log capacity.
- T9 input to register the employee name in the device.
- TCP/IP communication to real-time push attendance data to server.



Picture:

Cloud Connectivity

Auto-Push Technology

Realtime Monitoring



Specifications

■ Display	2.4-inch TFT LCD Color Screen
■ Proximity Card Capacity	10,000 125KHZ frequency card capacitive by default
■ Transaction Capacity	200,000
■ Communication	RS485, TCP/IP, USB-host
■ Functions	Record query, T9 input, Anti-passback, Scheduled-Bell, Anti-tamper, Cloud web(ADSM)
■ Access Control Interface	3rd Party Electric Lock, Door Sensor, Exit Button, Alarm, Doorbell
■ Wiegand Signal	Input, Output
■ Optional Functions	Wifi, Mifare, HID Card
■ SDK	Desktop & Cloud Web Based
■ Power Supply	12V 3A/5A DC
■ Operating Temperature	0°C - 45°C
■ Operating Humidity	20%-80%
■ Dimension (WxDxH)	187 X 77 X 33mm
■ Weight	530g

Accessories



Schematic diagram

